

## Rollex GRC Series Counting Scales – 3kg, 6kg, 12kg, 30kg

With high performance and accurate counting function plus flexible counting operation and an easy-to-use design. This model is not only equipped with 5 direct memory keys for unit weight setting but also stores up to 99 data accumulation and 45 data recall for the operator's conveniently use. Preset count and weight limits can be set to alarm the operator that a requested quantity or desired weight has been achieved.

### Features:

- Auto Zero Point Tracking
  - Tare Function
  - Energy-Saving Function
  - Low Power and Charging Status Indication
  - Counting Operations by Sample-quantity or Unit Weight Setting
  - Accumulation Function (up to 99 data accumulation and 45 data recall)
  - Quantity Alarm Setting
- Weight Checking Function (High/Low Limit Setting)  
Adjustable and Non-skid Rubber Feet  
In-use Cover for water-splash proof  
Stainless Steel Platter  
Options; LED Backlight, RS232 Interface

| Specifications:       | Model/Capacity  | Model  | Capacity | Division |      |      |
|-----------------------|---|--------|----------|----------|------|------|
|                       |   | GRC-3  | 3kg      | 1g       | 0.5g | 0.2g |
|                       |   | GRC-6  | 6kg      | 2g       | 1g   | 0.5g |
|                       |   | GRC-12 | 12kg     | 5g       | 2g   | 1g   |
|                       |   | GRC-30 | 30kg     | 10g      | 5g   | 2g   |
| Display               | 6,6,6 digits, LCD (18mm / 0.7")   |        |          |          |      |      |
| Keyboard              | 25 keys tactile   |        |          |          |      |      |
| Preset Memory Keys    | 5 keys  |        |          |          |      |      |
| Weighing Units        | Kg(g) / pcs   |        |          |          |      |      |
| Stabilization         | 3 sec   |        |          |          |      |      |
| Tare Range            | 100% of full scale capacity   |        |          |          |      |      |
| Calibration           | External calibration  |        |          |          |      |      |
| Operating Environment | Temperature : 0 °C ~ 40 °C (32 °F ~ 104 °F)<br>Humidity: < 80%  |        |          |          |      |      |
| Power Source          | DC: 4Ah/6V Rechargeable Battery<br>(160 hours without Backlight)<br>AC: 110V or 220V ± 10%, 60Hz/50Hz |        |          |          |      |      |
| Overall Dimensions    | Scale: 300mm x 330mm x 120mm (W x D x H)<br>Platter: 300mm x 240mm (W x D)                            |        |          |          |      |      |

